

BRYAN BOILERS

CLM - WEB
DATE: 07/15/14

Originators of the "Flexible Water Tube"

**WEBSTER BASE BURNER DATA
"CLM" SERIES BOILERS
NATURAL GAS / No. 2 OIL**

BOILER MODEL	INPUT		BASE BURNER MODEL (1)	COMBUSTION CONTROL MODEL/SCANNER (2)		IGNITION MEANS (3)		MOTOR DATA (4) HP	FIRING SYSTEM GAS	"UL" GAS TRAIN			OIL DATA	
	MBH	GPH		GAS & GAS / OIL	OIL	GAS & G/O	OIL			TRAIN SIZE NPT (6)	STANDARD PRESS IN. W.C./PSI		PUMP LOC (5)	SUC. GEAR CAP (GPH)
											MIN	MAX		
CLM 120	1200	8.6	JB1 - **	RM7897C/UV	R7284A/CC	GP	DS	1/3	LO-HI-OFF	1-1/4"	7.0"	14.0"	BM	45
CLM 150	1500	10.7	JB1 - **	RM7897C/UV	R7284A/CC	GP	DS	1/3	LO-HI-OFF	1-1/2"	7.0"	14.0"	BM	45
CLM 180	1800	12.9	JB1 - **	RM7897C/UV	R7284A/CC	GP	DS	1/2	LO-HI-OFF	1-1/2"	7.0"	14.0"	BM	70
CLM 210	2100	15.0	JB1 - **	RM7897C/UV	RM7897C/UV	GP	DS	1/2	LO-HI-OFF	2"	7.0"	14.0"	BM	70
CLM 240	2400	17.1	JB1 - **	RM7897C/UV	RM7897C/UV	GP	DS	3/4	LO-HI-OFF	2"	7.0"	14.0"	BM	70
CLM270	2700	19.3	JB2 - **	RM7897C/UV	RM7897C/UV	GP	DS	3/4	LO-HI-OFF	2"	7.0"	14.0"	BM	70
CLM300	3000	21.4	JB2 - **	RM7897C/UV	RM7897C/UV	GP	DS	1	LO-HI-OFF	2"	8.0"	14.0"	BM	70

STANDARD GAS TRAIN COMPONENTS

COMPONENT	CLM 120 to 180	CLM 210 & 240	CLM 270 & 300
Manual Shutoff Valve (point of field connection)	STD.	STD.	STD.
Gas Pressure Regulator	STD.	STD.	STD.
Main Oper. Gas Valve - Diaphragm type	STD.	N/A	N/A
Main Oper. Gas Valve - Motorized type	OPT.	STD.	STD.
Auxiliary Oper. Gas Valve - Solenoid type	STD.	STD.	STD.
Low Gas Pressure Switch	OPT.	OPT.	STD.
High Gas Pressure Switch	OPT.	OPT.	STD.
Manual Checking Shutoff Gas Valve	STD.	STD.	STD.

STANDARD OIL COMPONENTS

Dual Shutoff Valves	STD.	STD.	STD.
---------------------	------	------	------

ABBREVIATIONS:

(1)** Insert:: "G" - Gas, "C" - Gas/Oil, "O" = Oil

(2) Combustion Control:

Model - R7284A
Model - RM7897C

Scanner - "UV" = Ultra Violet
"CC" = Cad Cell

(3) Ignition means:

"GP" - Gas Pilot
"DS" - Direct Spark

(4) Motor Voltage: 60 Hz - Motor RPM: 3450 RPM

1/3 HP & 1/2 HP = 120/1 Ph
3/4 HP & 1 HP = 230/1/Ph

1 1/2 HP & Larger = 208-240-480/3 Ph (please specify)

(5) Oil Pump Location:

"BM" - Burner Mounted
"RM" - Remote Mounted



NOTES

>>>



1. Burner capacities listed for elevations up to 2,000 ft. For higher elevations, consult local Bryan Boilers sales office.
2. Oil ratings based on No. 2 fuel with heating value of 140,000 Btu per gallon.
3. Gas rating based on natural gas with heating value of 1000 Btu per cubic foot and specific gravity of .60. Gas burners for other gases are available, consult local Bryan Boilers sales office.



783 N. Chili Ave., Peru, Indiana 46970
Telephone: (765) 473-6651
Fax: (765) 473-3074
E-Mail: inquiry@bryansteam.com
Internet: www.bryanboilers.com